

Myrtle Point School District 41

Code: **EEAC**
Adopted: 2/8/99
Readopted: 1/12/09
Orig. Code(s): EEAC

School Bus Safety Program

The superintendent will ensure instruction for all students in school bus safety and emergency evacuation procedures is provided.

Buses will not exceed vehicle design capacity for seating at any time unless an unforeseen or unusual circumstance arises. Passengers will be provided a seat that fully supports them. A seat that fully supports each person and meets the minimum standards and specifications of law will be provided at all times. A person who weighs 40 pounds or less must be properly secured with a child safety system that meets the minimum standards and specifications established by the Department of Transportation under ORS 815.055. A person who weighs more than 40 pounds, who is four feet nine inches or shorter and under eight years of age must be properly secured with a child safety system that elevates the person so that a safety belt or safety harness properly fits the person.¹ A person who is taller than four feet nine inches or eight years of age or older must be properly secured with a safety belt or harness that meets the requirements under ORS 815.055. In accordance with ORS 811.210 and 811.215 vehicles used for student transportation in excess of 10,000 pounds are exempt from this requirement unless they have been equipped with lap belts. Vehicles in excess of 10,000 pounds that have been equipped with lap belts must meet child car seat requirements as set forth in law.

During adverse weather conditions, the superintendent may alter bus schedules or temporarily suspend bus services. The superintendent or his/her designee will advise local radio stations and other media of any changes in bus schedules or services.

In the case of emergency or disaster, evacuation of students will be carried out according to the district's emergency plan.

An accident review board will study accidents involving district buses and will make recommendations to avoid similar accidents.

END OF POLICY

Legal Reference(s):

[ORS 811.210](#)
[ORS 811.215](#)
[ORS 815.055](#)
[ORS 815.080](#)
[ORS 820.100 to-820.190](#)

[OAR 437-002-0220 to-0227](#)
[OAR 581-022-1420](#)

[OAR 581-053-0002 to-0015](#)
[OAR 581-053-0512 to-0555](#)
[OAR 735-102-0010](#)

¹“Proper fit” means the lap belt of the safety belt or safety harness is positioned low across the thighs and the shoulder belt is positioned over the collarbone and away from the neck.